

May 2, 2018

Request for Proposals (RFP): Professional Land Surveying Services

RFP No.: 2018-08

Franklin County, Missouri

Re: Proposed Adult Detention Facility Project

Your firm is being invited to submit statements of qualifications and proposals for providing Franklin County, Missouri with Professional Land Surveying services for the proposed Adult Detention Facility project.

Submissions will be accepted until 2:00pm CDT **May 9, 2018**. Please direct all questions to the Purchasing Department at purchasing@franklinmo.net. Any addenda to the RFP will be posted at the department's website, www.franklinmo.org/current, check frequently.

Please hand deliver or mail all proposals to the Purchasing Department no later than 2:00pm CDT on Wednesday, 05/09/18. The Purchasing Department is on the lowest level of the Franklin County Government Center located at 400 E Locust St, Room 004, Union, MO, 63084.

Scope of Work:

Franklin County, Missouri is procuring Professional Land Surveying services for the proposed Adult Detention Facility and Emergency Management/911 additions to the existing Franklin County Sheriff's Department located at 1 Bruns Drive, Union, MO, 63084.

The proposed Jail addition is expected to be 20' in height and designed to accommodate an additional 20' vertical addition in the next 20 years. The proposed EMA/911 addition is expected to be a one-story addition in alignment with the height of the existing Sheriff's Department structure. Attached is a proposed layout of the additions in relation to the exiting structures onsite. The topographic survey data obtained will be utilized by the County's design team to prepare design plans and specifications for the County's proposed additions to the existing Sheriff's Department and Adult Detention Facility.

The following services/tasks at a minimum, but not limited to, will need to be provided:

- 1) Complete a topographic survey for the area shown in the attached proposed site plan. This should include the following features:
 - Elevation points shall be taken every 100 feet along the center line and across the entire right-of way width, including spot grades at high points, low points and grade changes. Points required are located at the sidewalk, driveways and aprons, back of curb, edge of pavement flow line, centerline/concrete median etc. Topographic survey limits shall extend 10 feet beyond the project limits shown on the attached site plan.
 - All aboveground features, such as light poles, utility poles, traffic lights, mail boxes, sidewalks, fences, bushes, mature trees and saplings, signage, striping, overhead wires etc. inside the project limits and 10 feet beyond.

- Underground utilities, such as storm sewer, water main, water main services, sanitary sewer and their respective appurtenances, etc. (location and elevation of inverts, flow direction, size and material of pipes labeled in the CAD file).
 - Underground utilities, such as gas, electric, cable TV, telephone lines and their respective appurtenances (only location information for line work).
 - Right-of-Way, property lines and other survey markers, etc. The source of boundary line information shall be shown. Each property shall be labeled with its street address.
 - Identify all front and side yard utility easements identified in the title work.
- 2) Prepare an ALTA/NSPS Survey for the Parcel Number 17-6-23.0-0-099-032.000 with the address of 1 Bruns Lane, per the Franklin County Assessors Map in accordance with the “Minimum Standard Detail Requirements for ALTA/NSPS Land Title Surveys jointly established and adopted by ALTA and NSPS in 2016”, and including items 1, 2, 3, 4, 5, 7a, 8, 9, 11, 13, 16, 18 and 20 of the Table A attached herein. Client will provide title commitment and copies of Schedule B documents for any easements to be shown or noted on the survey.
- Item’s 5 and 8 of the above listed and attached requirements shall only be acquired/necessary on the area outlined in red and 10’ beyond on the attached exhibit. All other items shall encompass the entirety of the parcel.
 - Establish a Benchmark onsite. (NAVD 1988).
 - Prepare the base drawing of the survey in ACAD/Civil 3D format for incorporation into design plans.
 - Provide electronic drawings in a format compatible with the County’s civil design team including an existing 3D surface model with ground contours at 1-foot intervals generated from the field survey in the specified area. Items to be delivered on a USB Flash drive or approved equal.
 - Provide Two signed and sealed copies of the ALTA/NSPS Land Title Survey.
 - Include one (1) revision to ALTA survey per title objection letter.
- 3) Locate and identify a vertical datum and horizontal control points before the field work starts. The location and description of these and all benchmarks and horizontal control points set by the consultant shall be included and shown on the survey.
- 4) Shown survey points with elevation information shall be shown to the nearest one-hundredth of a foot for shots taken on hard surfaces and to the nearest one-tenth of a foot for shots taken on soft ground features.
- 5) The Consultant shall provide a brief report describing the equipment, software and procedures used to perform the survey. All surveying instruments shall be kept in proper adjustment and calibration.
- 6) All field notes shall be retained in a legible and orderly fashion that will be understandable to non-firm staff.
- 7) Next to the CAD file, an electronic PDF file copy of all field notes shall be submitted with the final drawings/survey.

Deliverables for the RFP:

- 1) Provide a summary of your approach to provide the appropriate professional land surveying services and recommendations for the County.
- 2) Proposed cost of services for work described herein. All reimbursable expenses including office supplies and travel expenses as well as a schedule of estimated man-hours/rates shall be included within the overall not-to-exceed cost.
- 3) Fee Schedule
- 4) Qualification submittals limited to no more than ten single-sided pages total in length; cover letter and table of contents are not included in the page count; resumes and copies of licenses are not included in the page count.
 - a. Discuss the qualifications of your firm and its ability to provide professional services for the proposed scope of work project types and scope delineated above. Particularly, discuss the following elements:
 - i. General Firm Information:
 1. List the general information of your firm, including legal name, mailing address, location, phone number, fax number and email address of firm/person submitting the qualifications.
 - ii. Relevant Project Experience:
 1. Include a summary of the Firm's history, experience and qualifications with projects (dates, description, locations, key personnel and references) similar to the project (Scope of Services). Emphasis should be given to projects performed from the local area office using staff nominated as available for this project.
 - iii. Key Personnel Qualifications:
 1. Include the names and resumes of the project manager and staff to be committed to the project. For each of the key personnel, identify their expected areas of responsibility and previous experience on similar projects.
 - iv. Capacity and Capability:
 1. Provide a narrative of how your firm will accomplish work in a timely manner and within project scheduling constraints. Demonstrate unique capabilities, innovative approaches, technical skills and systems, or special methodologies proposed to accomplish the work efficiently and to a high standard. Specifically list any work for which you do not have in-house capability, and name the firm you propose to subcontract for that work. Provide a systematic and methodical description as to how the scope of services will be accomplished in language suitable for inclusion in a legal contract.
 - v. Record of Performance:
 1. Provide a record of past performance with respect to control of costs, quality of work and ability to meet deadlines and schedules.

vi. Proximity and Familiarity:

1. List specific experience in dealing with local government agencies including: List projects conducted in the County of Franklin, Missouri (or surrounding area), if any, which may add to your knowledge, capability, and efficiency on this project.

vii. Additional Qualifications:

1. Indicate ability of the Firm to retain automobile and general liability insurance with umbrella coverage of \$3,000,000 per project and naming the County as an additional insured. Indicate your ability to retain professional liability insurance in the amount of \$1,000,000 per claim. Indicate your ability to retain Worker's Compensation insurance and your coverage limits.
 2. Upon selection of Firm, the Firm may be required to complete documents regarding enrollment in the Federal Work Authorization Program and E-Verify.
- 5) Please advise if there are any further services by your firm that should be provided as part of this scope that are not listed above that should be included in this scope and the reason behind your recommendation. Please include cost of such services if they are to be procured with this scope of work.

Project Schedule:

- | | |
|--|-----------------------------|
| 1) Receipt of Proposals | May 9, 2018 |
| 2) Evaluation & Recommendation to Commission | May 10, 2018 |
| 3) Commission Award of Proposal | May 15, 2018 |
| 4) Anticipate Title Work Received | May 25, 2018 |
| 5) Site Survey Scope of Work Performed | May 16, 2018 – June 1, 2018 |
| 6) Site Survey Documents Delivered to County | June 8, 2018 |

Kathy Hardeman, Purchasing Agent
Ann Struttmann, Assistant Purchasing Agent
Franklin County, Missouri
400 E Locust St, Room 004
Union, MO 63084
(636) 583-6274
purchasing@franklinmo.net

**MINIMUM STANDARD DETAIL REQUIREMENTS FOR
ALTA/NSPS LAND TITLE SURVEYS**
(Effective February 23, 2016)

NOTE - Attention is directed to the fact that the National Society of Professional Surveyors, Inc. (NSPS) is the legal successor organization to the American Congress on Surveying and Mapping (ACSM) and that these 2016 Minimum Standard Detail Requirements for ALTA/NSPS Land Title Surveys are the next version of the former Minimum Standard Detail Requirements for ALTA/ACSM Land Title Surveys.

1. Purpose - Members of the American Land Title Association® (ALTA®) have specific needs, unique to title insurance matters, when asked to insure title to land without exception as to the many matters which might be discoverable from survey and inspection, and which are not evidenced by the public records.

For a survey of real property, and the plat, map or record of such survey, to be acceptable to a title insurance company for the purpose of insuring title to said real property free and clear of survey matters (except those matters disclosed by the survey and indicated on the plat or map), certain specific and pertinent information must be presented for the distinct and clear understanding between the insured, the client (if different from the insured), the title insurance company (insurer), the lender, and the surveyor professionally responsible for the survey.

In order to meet such needs, clients, insurers, insureds, and lenders are entitled to rely on surveyors to conduct surveys and prepare associated plats or maps that are of a professional quality and appropriately uniform, complete, and accurate. To that end, and in the interests of the general public, the surveying profession, title insurers, and abstracters, the ALTA and the NSPS jointly promulgate the within details and criteria setting forth a minimum standard of performance for ALTA/NSPS Land Title Surveys. A complete 2016 ALTA/NSPS Land Title Survey includes:

- (i) the on-site fieldwork required pursuant to Section 5,
- (ii) the preparation of a plat or map pursuant to Section 6 showing the results of the fieldwork and its relationship to documents provided to or obtained by the surveyor pursuant to Section 4,
- (iii) any information from Table A items requested by the client, and
- (iv) the certification outlined in Section 7.

2. Request for Survey - The client shall request the survey, or arrange for the survey to be requested, and shall provide a written authorization to proceed from the person or entity responsible for paying for the survey. Unless specifically authorized in writing by the insurer, the insurer shall not be responsible for any costs associated with the preparation of the survey. The request shall specify that an "ALTA/NSPS LAND TITLE SURVEY" is required and which of the optional items listed in Table A, if any, are to be incorporated. Certain properties or interests in real properties may present issues outside those normally encountered on an ALTA/NSPS Land Title Survey (e.g., marinas, campgrounds, trailer parks; easements, leases, other non-fee simple interests). The scope of work related to surveys of such properties or interests in real properties should be discussed with the client, lender, and insurer; and agreed upon in writing prior to commencing work on the survey. The client may need to secure permission for the surveyor to enter upon the property to be surveyed, adjoining properties, or offsite easements.

3. Surveying Standards and Standards of Care

- A. Effective Date** - The 2016 Minimum Standard Detail Requirements for ALTA/NSPS Land Title Surveys are effective February 23, 2016. As of that date, all previous versions of the Minimum Standard Detail Requirements for ALTA/ACSM Land Title Surveys are superseded by these standards.
- B. Other Requirements and Standards of Practice** - Many states and some local jurisdictions have adopted statutes, administrative rules, and/or ordinances that set out standards regulating the practice of surveying within their jurisdictions. In addition to the standards set forth herein, surveyors shall also conduct their surveys in accordance with applicable jurisdictional survey requirements and standards of practice. Where conflicts between the standards set forth herein and any such jurisdictional requirements and standards of practice occur, the more stringent shall apply.
- C. The Normal Standard of Care** - Surveyors should recognize that there may be unwritten local, state, and/or regional standards of care defined by the practice of the "prudent surveyor" in those locales.
- D. Boundary Resolution** - The boundary lines and corners of any property being surveyed as part of an ALTA/NSPS Land Title Survey shall be established and/or retraced in accordance with appropriate boundary law principles governed by the set of facts and evidence found in the course of performing the research and fieldwork.
- E. Measurement Standards** - The following measurement standards address Relative Positional Precision for the monuments or witnesses marking the corners of the surveyed property.
- i. "Relative Positional Precision" means the length of the semi-major axis, expressed in feet or meters, of the error ellipse representing the uncertainty due to random errors in measurements in the location of the monument, or witness, marking any corner of the surveyed property relative to the monument, or witness, marking any other corner of the surveyed property at the 95 percent confidence level. Relative Positional Precision is estimated by the results of a correctly weighted least squares adjustment of the survey.
 - ii. Any boundary lines and corners established or retraced may have uncertainties in location resulting from (1) the availability, condition, history and integrity of reference or controlling monuments, (2) ambiguities in the record descriptions or plats of the surveyed property or its adjoining, (3) occupation or possession lines as they may differ from the written title lines, or (4) Relative Positional Precision. Of these four sources of uncertainty, only Relative Positional Precision is controllable, although, due to the inherent errors in any measurement, it cannot be eliminated. The magnitude of the first three uncertainties can be projected based on evidence; Relative Positional Precision is estimated using statistical means (see Section 3.E.i. above and Section 3.E.v. below).
 - iii. The first three of these sources of uncertainty must be weighed as part of the evidence in the determination of where, in the surveyor's opinion, the boundary lines and corners of the surveyed property should be located (see Section 3.D. above). Relative Positional Precision is a measure of how precisely the surveyor is able to monument and report those positions; it is not a substitute for the application of proper boundary law principles. A boundary corner or line may have a small Relative Positional Precision because the survey measurements were precise, yet still be in the wrong position (*i.e.*, inaccurate) if it was established or retraced using faulty or improper application of boundary law principles.
 - iv. For any measurement technology or procedure used on an ALTA/NSPS Land Title Survey, the surveyor shall (1) use appropriately trained personnel, (2) compensate for systematic errors, including those associated with instrument calibration, and (3) use appropriate error propagation and measurement design theory (selecting the proper instruments, geometric layouts, and field and computational procedures) to control random errors such that the

maximum allowable Relative Positional Precision outlined in Section 3.E.v. below is not exceeded.

- v. The maximum allowable Relative Positional Precision for an ALTA/NSPS Land Title Survey is 2 cm (0.07 feet) plus 50 parts per million (based on the direct distance between the two corners being tested). It is recognized that in certain circumstances, the size or configuration of the surveyed property, or the relief, vegetation, or improvements on the surveyed property, will result in survey measurements for which the maximum allowable Relative Positional Precision may be exceeded. If the maximum allowable Relative Positional Precision is exceeded, the surveyor shall note the reason as explained in Section 6.B.x. below.

4. Records Research - It is recognized that for the performance of an ALTA/NSPS Land Title Survey, the surveyor will be provided with appropriate and, when possible, legible data which can be relied upon in the preparation of the survey. The request for an ALTA/NSPS Land Title Survey shall set forth the current record description of the property to be surveyed or, in the case of an original survey prepared for purposes of locating and describing real property that has not been previously separately described in documents conveying an interest in the real property, the current record description of the parent parcel that contains the property to be surveyed.

In order to complete an ALTA/NSPS Land Title Survey, the surveyor must be provided with complete copies of the most recent title commitment or, if a title commitment is not available, other title evidence satisfactory to the title insurer. In addition, the surveyor must be provided with the following:

- (i) The following records established under state statutes for the purpose of imparting constructive notice of matters relating to real property (public records):
 - (a) The current record descriptions of any adjoining to the property to be surveyed, except where such adjoining are lots in platted, recorded subdivisions;
 - (b) Any recorded easements benefitting the property;
 - (c) Any recorded easements, servitudes, or covenants burdening the property;
- (ii) Any unrecorded documents affecting the property being surveyed and containing information to which the survey shall make reference, if desired by the client.

Except, however, if the documents outlined above in (i) and (ii) of this section are not provided to the surveyor or if non-public or quasi-public documents are required to complete the survey, the surveyor shall be required to conduct only that research which is required pursuant to the statutory or administrative requirements of the jurisdiction where the property being surveyed is located and that research (if any) which is negotiated and outlined in the terms of the contract between the surveyor and the client.

5. Fieldwork - The survey shall be performed on the ground (except as otherwise negotiated pursuant to Table A, Item 15 below, if selected by the client). The fieldwork shall include the following, located to what is, in the surveyor's professional opinion, the appropriate degree of precision based on (a) the planned use of the property, if reported in writing to the surveyor by the client, lender, or insurer, or (b) the existing use, if the planned use is not so reported:

A. Monuments

- i. The location, size, character, and type of any monuments found during the fieldwork.
- ii. The location, size, character, and type of any monuments set during the fieldwork, if item 1 of Table A was selected or if otherwise required by applicable jurisdictional requirements and/or standards of practice.
- iii. The location, description, and character of any lines that control the boundaries of the

surveyed property.

B. Rights of Way and Access

- i. The distance from the appropriate corner or corners of the surveyed property to the nearest right of way line, if the surveyed property does not abut a right of way.
- ii. The name of any street, highway, or other public or private way abutting the surveyed property, together with the width of the travelled way and the location of each edge of the travelled way including on divided streets and highways. If the documents provided to or obtained by the surveyor pursuant to Section 4 indicate no access from the surveyed property to the abutting street or highway, the width and location of the travelled way need not be located.
- iii. Visible evidence of physical access (*e.g.*, curb cuts, driveways) to any abutting streets, highways, or other public or private ways.
- iv. The location and character of vehicular, pedestrian, or other forms of access by other than the apparent occupants of the surveyed property to or across the surveyed property observed in the process of conducting the fieldwork (*e.g.*, driveways, alleys, private roads, railroads, railroad sidings and spurs, sidewalks, footpaths).
- v. Without expressing a legal opinion as to ownership or nature, the location and extent of any potentially encroaching driveways, alleys, and other ways of access from adjoining properties onto the surveyed property observed in the process of conducting the fieldwork.
- vi. Where documentation of the location of any street, road, or highway right of way abutting, on, or crossing the surveyed property was not disclosed in documents provided to or obtained by the surveyor, or was not otherwise available from the controlling jurisdiction (see Section 6.C.iv. below), the evidence and location of parcel corners on the same side of the street as the surveyed property recovered in the process of conducting the fieldwork which may indicate the location of such right of way lines (*e.g.*, lines of occupation, survey monuments).
- vii. Evidence of access to and from waters adjoining the surveyed property observed in the process of conducting the fieldwork (*e.g.*, paths, boat slips, launches, piers, docks).

C. Lines of Possession and Improvements along the Boundaries

- i. The character and location of evidence of possession or occupation along the perimeter of the surveyed property, both by the occupants of the surveyed property and by adjoining, observed in the process of conducting the fieldwork.
- ii. Unless physical access is restricted, the character and location of all walls, buildings, fences, and other improvements within five feet of each side of the boundary lines, observed in the process of conducting the fieldwork. Trees, bushes, shrubs, and other natural vegetation need not be located other than as specified in the contract, unless they are deemed by the surveyor to be evidence of possession pursuant to Section 5.C.i.
- iii. Without expressing a legal opinion as to the ownership or nature of the potential encroachment, the evidence, location and extent of potentially encroaching structural appurtenances and projections observed in the process of conducting the fieldwork (*e.g.*, fire escapes, bay windows, windows and doors that open out, flue pipes, stoops, eaves, cornices, areaways, steps, trim) by or onto adjoining property, or onto rights of way, easements, or setback lines disclosed in documents provided to or obtained by the surveyor.

D. Buildings

The location of buildings on the surveyed property observed in the process of conducting the fieldwork.

E. Easements and Servitudes

- i. Evidence of any easements or servitudes burdening the surveyed property as disclosed in the documents provided to or obtained by the surveyor pursuant to Section 4 and observed in the process of conducting the fieldwork.

- ii. Evidence of easements, servitudes, or other uses by other than the apparent occupants of the surveyed property not disclosed in the documents provided to or obtained by the surveyor pursuant to Section 4, but observed in the process of conducting the fieldwork if they appear to affect the surveyed property (e.g., roads; drives, sidewalks, paths and other ways of access; utility service lines; water courses; ditches; drains; telephone, fiber optic lines, or electric lines; or water, sewer, oil or gas pipelines on or across the surveyed property and on adjoining properties).
- iii. Surface indications of underground easements or servitudes on or across the surveyed property observed in the process of conducting the fieldwork (e.g., utility cuts, vent pipes, filler pipes).
- iv. Evidence on or above the surface of the surveyed property observed in the process of conducting the fieldwork, which evidence may indicate utilities located on, over or beneath the surveyed property. Examples of such evidence include pipeline markers, manholes, valves, meters, transformers, pedestals, clean-outs, utility poles, overhead lines and guy wires.

F. Cemeteries

As accurately as the evidence permits, the perimeter of cemeteries and burial grounds, and the location of isolated gravesites not within a cemetery or burial ground, (i) disclosed in the documents provided to or obtained by the surveyor, or (ii) observed in the process of conducting the fieldwork.

G. Water Features

- i. The location of springs, ponds, lakes, streams, rivers, canals, ditches, marshes, and swamps on, running through, or outside, but within five feet of the perimeter boundary of, the surveyed property, observed during the process of conducting the fieldwork.
- ii. The location of any water feature forming a boundary of the surveyed property. The attribute(s) of the water feature located (e.g., top of bank, edge of water, high water mark) should be congruent with the boundary as described in the record description or, in the case of an original survey, in the new description (see Section 6.B.vi. below).

6. Plat or Map - A plat or map of an ALTA/NSPS Land Title Survey shall show the following information. Where dimensioning is appropriate, dimensions shall be annotated to what is, in the surveyor's professional opinion, the appropriate degree of precision based on (a) the planned use of the property, if reported in writing to the surveyor by the client, lender, or insurer, or (b) existing use, if the planned use is not so reported.

A. The evidence and locations gathered, and the monuments and lines located during the fieldwork pursuant to Section 5 above, with accompanying notes if deemed necessary by the surveyor or as otherwise required as specified below.

B. Boundary, Descriptions, Dimensions, and Closures

- i. (a) The current record description of the surveyed property, or
(b) In the case of an original survey, the current record description of the parent tract that contains the surveyed property.
- ii. Any new description of the surveyed property that was prepared in conjunction with the survey, including a statement explaining why the new description was prepared. Except in the case of an original survey, preparation of a new description should be avoided unless deemed necessary or appropriate by the surveyor and insurer. Preparation of a new description should also generally be avoided when the record description is a lot or block in a platted, recorded subdivision. Except in the case of an original survey, if a new description is prepared, a note shall be provided stating (a) that the new description describes the same real estate as the record description or, if it does not, (b) how the new description differs from

- the record description.
- iii. The point of beginning, the remote point of beginning or point of commencement (if applicable) and all distances and directions identified in the record description of the surveyed property (and in the new description, if one was prepared). Where a measured or calculated dimension differs from the record by an amount deemed significant by the surveyor, such dimension shall be shown in addition to, and differentiated from, the corresponding record dimension. All dimensions shown on the survey and contained in any new description shall be ground dimensions unless otherwise noted.
 - iv. The directional, distance and curve data necessary to compute a mathematical closure of the surveyed boundary. A note if the record description does not mathematically close. The basis of bearings and, where it differs from the record basis, the difference.
 - v. The remainder of any recorded lot or existing parcel, when the surveyed property is composed of only a portion of such lot or parcel, shall be graphically depicted. Such remainder need not be included as part of the actual survey, except to the extent necessary to locate the lines and corners of the surveyed property, and it need not be fully dimensioned or drawn at the same scale as the surveyed property.
 - vi. When the surveyed property includes a title line defined by a water boundary, a note on the face of the plat or map noting the date the boundary was measured, which attribute(s) of the water feature was/were located, and the caveat that the boundary is subject to change due to natural causes and that it may or may not represent the actual location of the limit of title. When the surveyor is aware of natural or artificial realignments or changes in such boundaries, the extent of those changes and facts shall be shown or explained.
 - vii. The relationship of the boundaries of the surveyed property with its adjoining (e.g., contiguity, gaps, overlaps), where ascertainable from documents provided to or obtained by the surveyor pursuant to Section 4 and/or from field evidence gathered during the process of conducting the fieldwork. If the surveyed property is composed of multiple parcels, the extent of any gaps or overlaps between those parcels shall be identified. Where gaps or overlaps are identified, the surveyor shall, prior to or upon delivery of the final plat or map, disclose this to the insurer and client.
 - viii. When, in the opinion of the surveyor, the results of the survey differ significantly from the record, or if a fundamental decision related to the boundary resolution is not clearly reflected on the plat or map, the surveyor shall explain this information with notes on the face of the plat or map.
 - ix. The location of all buildings on the surveyed property, located pursuant to Section 5.D., dimensioned perpendicular to those perimeter boundary lines that the surveyor deems appropriate (i.e., where potentially impacted by a setback line) and/or as requested by the client, lender or insurer.
 - x. A note on the face of the plat or map explaining the site conditions that resulted in a Relative Positional Precision that exceeds the maximum allowed pursuant to Section 3.E.v.
 - xi. A note on the face of the plat or map identifying areas, if any, on the boundaries of the surveyed property, to which physical access within five feet was restricted (see Section 5.C.ii.).
 - xii. A note on the face of the plat or map identifying the source of the title commitment or other title evidence provided pursuant to Section 4, and the effective date and the name of the insurer of same.

C. Easements, Servitudes, Rights of Way, Access, and Documents

- i. The location, width, and recording information of all plottable rights of way, easements, and servitudes burdening and benefitting the property surveyed, as evidenced by documents provided to or obtained by the surveyor pursuant to Section 4.

- ii. A summary of all rights of way, easements and servitudes burdening the property surveyed and identified in the title evidence provided to or obtained by the surveyor pursuant to Section 4. Such summary shall include the record information of each such right of way, easement or servitude, a statement indicating whether or not it is shown on the plat or map, and a related note if:
 - (a) the location cannot be determined from the record document;
 - (b) there was no observed evidence at the time of the fieldwork;
 - (c) it is a blanket easement;
 - (d) it is not on, or does not touch, the surveyed property;
 - (e) it limits access to an otherwise abutting right of way;
 - (f) the documents are illegible; or
 - (g) the surveyor has information indicating that it may have been released or otherwise terminated.

In cases where the surveyed property is composed of multiple parcels, indicate which of such parcels the various rights of way, easements, and servitudes cross or touch.

- iii. A note if no physical access to a public way was observed in the process of conducting the fieldwork.
- iv. The locations and widths of rights of way abutting or crossing the surveyed property, and the source of such information, (a) where available from the controlling jurisdiction, or (b) where disclosed in documents provided to or obtained by the surveyor pursuant to Section 4.
- v. The identifying titles of all recorded plats, filed maps, right of way maps, or similar documents which the survey represents, wholly or in part, with their recording or filing data.
- vi. For non-platted adjoining land, recording data identifying adjoining tracts according to current public records. For platted adjoining land, the recording data of the subdivision plat.
- vii. Platted setback or building restriction lines which appear on recorded subdivision plats or which were disclosed in documents provided or obtained by the surveyor.

D. Presentation

- i. The plat or map shall be drawn on a sheet of not less than 8 ½ by 11 inches in size at a legible, standard engineering scale, with that scale clearly indicated in words or numbers and with a graphic scale.
- ii. The plat or map shall include:
 - (a) The boundary of the surveyed property drawn in a manner that distinguishes it from other lines on the plat or map.
 - (b) If no buildings were observed on the surveyed property in the process of conducting the fieldwork, a note stating "*No buildings observed.*"
 - (c) A north arrow (with north to the top of the drawing when practicable).
 - (d) A legend of symbols and abbreviations.
 - (e) A vicinity map showing the property in reference to nearby highway(s) or major street intersection(s).
 - (f) Supplementary or detail diagrams when necessary.
 - (g) Notes explaining any modifications to Table A items and the nature of any additional Table A items (e.g., 21(a), 21(b), 21(c)) that were negotiated between the surveyor and client.
 - (h) The surveyor's project number (if any), and the name, registration or license number, signature, seal, street address, telephone number, company website, and email address (if any) of the surveyor who performed the survey.
 - (i) The date(s) of any revisions made by the surveyor who performed the survey.
 - (j) Sheet numbers where the plat or map is composed of more than one sheet.
 - (k) The caption "ALTA/NSPS Land Title Survey."

iii. When recordation or filing of a plat or map is required by law, such plat or map shall be produced in recordable form.

7. **Certification** - The plat or map of an ALTA/NSPS Land Title Survey shall bear only the following certification, unaltered, except as may be required pursuant to Section 3.B. above:

To (name of insured, if known), (name of lender, if known), (name of insurer, if known), (names of others as negotiated with the client):

This is to certify that this map or plat and the survey on which it is based were made in accordance with the 2016 Minimum Standard Detail Requirements for ALTA/NSPS Land Title Surveys, jointly established and adopted by ALTA and NSPS, and includes Items _____ of Table A thereof. The fieldwork was completed on _____ [date].

Date of Plat or Map: _____ (Surveyor's signature, printed name and seal with Registration/License Number)

8. **Deliverables** - The surveyor shall furnish copies of the plat or map of survey to the insurer and client and as otherwise negotiated with the client. Hard copies shall be on durable and dimensionally stable material of a quality standard acceptable to the insurer. A digital image of the plat or map may be provided in addition to, or in lieu of, hard copies pursuant to the terms of the contract. When required by law or requested by the client, the plat or map shall be produced in recordable form and recorded or filed in the appropriate office or with the appropriate agency.

TABLE A

OPTIONAL SURVEY RESPONSIBILITIES AND SPECIFICATIONS

NOTE: The twenty (20) items of Table A may be negotiated between the surveyor and client. Any additional items negotiated between the surveyor and client shall be identified as 21(a), 21(b), etc. and explained pursuant to Section 6.D.ii.(g). Notwithstanding Table A Items 5 and 11, if an engineering design survey is desired as part of an ALTA/NSPS Land Title Survey, such services should be negotiated under Table A, Item 21.

If checked, the following optional items are to be included in the ALTA/NSPS LAND TITLE SURVEY, except as otherwise qualified (see note above):

1. Monuments placed (or a reference monument or witness to the corner) at all major corners of the boundary of the property, unless already marked or referenced by existing monuments or witnesses in close proximity to the corner.
2. Address(es) of the surveyed property if disclosed in documents provided to or obtained by the surveyor, or observed while conducting the fieldwork.
3. Flood zone classification (with proper annotation based on federal Flood Insurance Rate Maps or the state or local equivalent) depicted by scaled map location and graphic plotting only.
4. Gross land area (and other areas if specified by the client).
5. Vertical relief with the source of information (e.g., ground survey, aerial map), contour interval, datum, and originating benchmark identified.
6. (a) If set forth in a zoning report or letter provided to the surveyor by the client, list the current zoning classification, setback requirements, the height and floor space area restrictions, and parking requirements. Identify the date and source of the report or letter.
 (b) If the zoning setback requirements are set forth in a zoning report or letter provided to the surveyor by the client, and if those requirements do not require an interpretation by the surveyor, graphically depict the building setback requirements. Identify the date and source of the report or letter.
7. (a) Exterior dimensions of all buildings at ground level.
 (b) Square footage of:
 (1) exterior footprint of all buildings at ground level.
 (2) other areas as specified by the client.
 (c) Measured height of all buildings above grade at a location specified by the client. If no location is specified, the point of measurement shall be identified.

8. Substantial features observed in the process of conducting the fieldwork (in addition to the improvements and features required pursuant to Section 5 above) (e.g., parking lots, billboards, signs, swimming pools, landscaped areas, substantial areas of refuse).
9. Number and type (e.g., disabled, motorcycle, regular and other marked specialized types) of clearly identifiable parking spaces on surface parking areas, lots and in parking structures. Striping of clearly identifiable parking spaces on surface parking areas and lots.
10. (a) As designated by the client, a determination of the relationship and location of certain division or party walls with respect to adjoining properties (client to obtain necessary permissions).
- (b) As designated by the client, a determination of whether certain walls are plumb (client to obtain necessary permissions).
11. Location of utilities existing on or serving the surveyed property as determined by:
- observed evidence collected pursuant to Section 5.E.iv.
 - evidence from plans requested by the surveyor and obtained from utility companies, or provided by client (with reference as to the sources of information), and
 - markings requested by the surveyor pursuant to an 811 utility locate or similar request
- Representative examples of such utilities include, but are not limited to:
- Manholes, catch basins, valve vaults and other surface indications of subterranean uses;
 - Wires and cables (including their function, if readily identifiable) crossing the surveyed property, and all poles on or within ten feet of the surveyed property. Without expressing a legal opinion as to the ownership or nature of the potential encroachment, the dimensions of all encroaching utility pole crossmembers or overhangs; and
 - Utility company installations on the surveyed property.
- Note to the client, insurer, and lender - With regard to Table A, item 11, source information from plans and markings will be combined with observed evidence of utilities pursuant to Section 5.E.iv. to develop a view of the underground utilities. However, lacking excavation, the exact location of underground features cannot be accurately, completely, and reliably depicted. In addition, in some jurisdictions, 811 or other similar utility locate requests from surveyors may be ignored or result in an incomplete response, in which case the surveyor shall note on the plat or map how this affected the surveyor's assessment of the location of the utilities. Where additional or more detailed information is required, the client is advised that excavation and/or a private utility locate request may be necessary.
12. As specified by the client, Governmental Agency survey-related requirements (e.g., HUD surveys, surveys for leases on Bureau of Land Management managed lands).

-
13. Names of adjoining owners according to current tax records. If more than one owner, identify the first owner's name listed in the tax records followed by "et al."
14. As specified by the client, distance to the nearest intersecting street.
15. Rectified orthophotography, photogrammetric mapping, remote sensing, airborne/mobile laser scanning and other similar products, tools or technologies as the basis for the showing the location of certain features (excluding boundaries) where ground measurements are not otherwise necessary to locate those features to an appropriate and acceptable accuracy relative to a nearby boundary. The surveyor shall (a) discuss the ramifications of such methodologies (e.g., the potential precision and completeness of the data gathered thereby) with the insurer, lender, and client prior to the performance of the survey, and (b) place a note on the face of the survey explaining the source, date, precision, and other relevant qualifications of any such data.
16. Evidence of recent earth moving work, building construction, or building additions observed in the process of conducting the fieldwork.
17. Proposed changes in street right of way lines, if such information is made available to the surveyor by the controlling jurisdiction. Evidence of recent street or sidewalk construction or repairs observed in the process of conducting the fieldwork.
18. If there has been a field delineation of wetlands conducted by a qualified specialist hired by the client, the surveyor shall locate any delineation markers observed in the process of conducting the fieldwork and show them on the face of the plat or map. If no markers were observed, the surveyor shall so state.
19. Include any plottable offsite (i.e., appurtenant) easements or servitudes disclosed in documents provided to or obtained by the surveyor as a part of the survey pursuant to Sections 5 and 6 (and applicable selected Table A items) (client to obtain necessary permissions).
20. Professional Liability Insurance policy obtained by the surveyor in the minimum amount of \$2,000,000 to be in effect throughout the contract term. Certificate of Insurance to be furnished upon request, but this item shall not be addressed on the face of the plat or map.
21.
-

Adopted by the Board of Governors, American Land Title Association, on October 8, 2015.
American Land Title Association, 1800 M St., N.W., Suite 300S, Washington, D.C. 20036-5828.
www.alta.org

Adopted by the Board of Directors, National Society of Professional Surveyors, on October 9, 2015.
National Society of Professional Surveyors, Inc., 5119 Pegasus Court, Suite Q, Frederick, MD 21704.
<http://www.nspss.us.com/>

ChiodiniArchitects | GGA

Conceptual Site Plan

